

(19) 世界知的所有権機関  
国際事務局



(43) 国際公開日  
2004 年 10 月 21 日 (21.10.2004)

PCT


(10) 国際公開番号  
WO 2004/091198 A1

- (51) 国際特許分類<sup>7</sup>: H04N 5/45
- (21) 国際出願番号: PCT/JP2004/004780
- (22) 国際出願日: 2004 年 4 月 1 日 (01.04.2004)
- (25) 国際出願の言語: 日本語
- (26) 国際公開の言語: 日本語
- (30) 優先権データ:  
特願2003-105022 2003 年 4 月 9 日 (09.04.2003) JP
- (71) 出願人 (米国を除く全ての指定国について): 松下電器産業株式会社 (MATSUSHITA ELECTRIC INDUSTRIAL CO., LTD.) [JP/JP]; 〒5718501 大阪府門真市大字門真 1006 番地 Osaka (JP).
- (72) 発明者; および
- (75) 発明者/出願人 (米国についてのみ): 米野 潤一 (KOMENO, Junichi).
- (74) 代理人: 松田 正道 (MATSUDA, Masamichi); 〒5320003 大阪府大阪市淀川区宮原 5 丁目 1 番 3 号 新大阪生島ビル Osaka (JP).
- (81) 指定国 (表示のない限り、全ての種類の国内保護が可能): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) 指定国 (表示のない限り、全ての種類の広域保護が可能): ARIPO (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), ユーラシア (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), ヨーロッパ (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC,

[続葉有]

(54) Title: OSD-SYNTHESIZED IMAGE DECODING DEVICE, OSD-SYNTHESIZED IMAGE DECODING METHOD, PROGRAM, AND RECORDING MEDIUM

(54) 発明の名称: OSD合成画像復号装置、OSD合成画像復号方法、プログラム、記録媒体



91...IMAGE DECODING MEANS  
11...HIGH-RESOLUTION MPEG2 DECODER  
12...LOW-RESOLUTION MPEG2 DECODER  
20...IMAGE INPUT SELECTOR  
40...1080i IMAGE RESOLUTION FORMAT CONVERTER  
A...1080i IMAGE  
B...OSD DATA  
51...OSD GENERATOR  
50...OSD SYNTHESIZER

85...SYSTEM LSI  
60...480p IMAGE RESOLUTION FORMAT CONVERTER  
61...480i IMAGE RESOLUTION FORMAT CONVERTER  
70...IMAGE OUTPUT SELECTOR  
C...SWITCHING SIGNAL  
30...MICROCOMPUTER  
D...IMAGE RESOLUTION FORMAT SWITCHING SIGNAL  
95...IMAGE RESOLUTION FORMAT SETTING MEANS

(57) Abstract: When a plurality of display devices having different image resolution formats are simultaneously connected, it is impossible to simultaneously output image data of different image resolution formats. An OSD-synthesized image decoding device includes: selection means (20) for selecting a plurality of decoding image data; conversion means (40) for converting the selected decoding image data into 1080i; OSD generation means (51) for generating OSD for 1080i to

[続葉有]

## ABSTRACT

When connections are made to plural display devices having different image resolution formats at the same time, image data cannot be outputted in different image resolution formats at the same time.

An OSD composite image decoding apparatus includes: selection means 20 of selecting plural types of decoded image data; conversion means 40 of converting the selected decoded image data to 1080i; means 51 of generating OSD for 1080i to be synchronously superimposed on the format-converted image data; means 50 of superimposing the generated OSD for 1080i and the image data format-converted to the 1080i image resolution format on each other; means 60,61 of converting the superimposed 1080i image data to 480p or 480i; switching means 70 of switching between 1080i, 480p and 480i for each of output terminals; and processing means 30 of informing the selection means 20 of decoded image data desired to be decoded and instructing the switching means 70 to perform switching so that the decoded image data becomes suited to the image resolution format of an externally connected display device.